



58 Series Support Saddles



Description

The Buckaroos 58 Series Saddle is designed to provide proper support to insulated pipe at Clevis Hanger locations. Precision-formed from G-90 galvanized steel rolled into a 180-degree arc, this Galvanized saddle contains unique features that set it apart from similar looking, but lesser performing saddles. The 58 Series Saddle is a proven winner!

Features and Benefits

- Constructed of G-90 Galvanized Steel per ASTM A-527 for long-term durability.
- Precise manufacturing tolerances yield exact insulated outer diameter per the ASTM C-585 Standard Specification for a perfect fit.
- Available in 18-gauge through 12-gauge thickness for virtually every application.
- Each saddle is individually marked with the insulation outer diameter for easy jobsite identification.
- Also available as a 2-piece upper/lower unit for complete self-clamping 360-degree insulation protection.
- High-strength corrugated Kraft packaging with ten saddles per carton for maximum convenience and easy handling.

Technical Data

The Buckaroos 58 Series Support Saddles are constructed of G-90 galvanized steel, as per ASTM A-527. They are formed to fit the exact insulated outer diameters as per ASTM C-585.

Product Dimensions

Buckaroos 58 Series Support Saddles are ordered to conform to the sizing requirements of MSS SP-58 shown below.

Pipe Size	Saddle Gauge	Saddle Length
1/2" – 3 1/2"	18 Ga.	12"
4"	16 Ga.	12"
5" and 6"	16 Ga.	18"
8" – 14"	14 Ga.	24"
16" – 24"	12 Ga.	24"

The above table is based upon insulation compressive strength of 15 P.S.I. in clevis hangers. Higher compressive strength insulations can result in shorter saddle lengths. Consult your project specification.